



PRODUCT INFORMATION

a product of NITEO™ Products

PYROIL™ DOT 3 BRAKE FLUID

DESCRIPTION:

Pyroil DOT 3 Brake Fluid is a blend of premium grade glycols and glycol ethers with inhibitors for corrosion protection. **Pyroil DOT 3 Brake Fluid** is designed for use in braking systems fitted with rubber cups and seals made from natural rubber (NR), styrenebutadiene rubber (SBR), or a terpolymer of ethylene, propylene, and a diene (EPDM). Contaminants such as water, dirt, and petroleum products can severely damage the brake system.

Pyroil DOT 3 Brake Fluid is used to transmit pressure from the driver's foot to the wheel cylinders, where that pressure is then converted into a frictional braking force on the wheels. Frictional braking force creates heat, which can get transferred to the brake fluid itself. Vehicle manufacturers specify exactly which brake fluid to use.

Brake fluids attract moisture, so always store **Pyroil DOT 3 Brake Fluid** in a dry place with the cap securely tightened. Before opening the master cylinder, clean the surrounding area to prevent dirt or grease from contaminating the brake fluid. Do not open the master cylinder outdoors when it is raining or snowing. Do not open the master cylinder in an area of airborne dust or dirt. Check the fluid level and fill the reservoir to the level recommended by the vehicle manufacturer. Excellent for ABS, disc and drum brake systems.

Complies with Federal Motor Vehicle Safety Standard 116. Meets SAE J1703.

1. FOLLOW VEHICLE MANUFACTURER'S RECOMMENDATIONS WHEN ADDING BRAKE FLUID.
2. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs.
3. STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE.
4. CAUTION: DO NOT REFILL CONTAINER, AND DO NOT USE FOR OTHER LIQUIDS.



FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
12/1/2014	12/1/2019	3/1/2011	DET	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.



PRODUCT INFORMATION

a product of NITEO™ Products

Part Number	Description	Unit UPC
PYBF1	Pyroil DOT 3 Brake Fluid 4/1 Gallon	0 28882 10014 4
PYBF12	Pyroil DOT 3 Brake Fluid 12/12 oz	0 28882 10012 0
PYBF32	Pyroil DOT 3 Brake Fluid 12/32 oz	0 28882 10013 7

BENEFITS:

- Meets Federal Motor Vehicle Safety Standard (FMVSS) No. 116 And SAE J1703 Specifications
- Provides Superior Braking Power
- Low Moisture Content
- Mixes With Conventional DOT 3 Brake Fluid

TECHNICAL DATA:

Appearance	Clear Liquid
Dry Boiling Point, °F (°C) (ERBP), min	401 °F (205 °C)
Wet Boiling Point, °F (°C) (ERBP), min	284 °F (140 °C)
Plastic Safe	Yes
Flash Point	250 °F Closed Cup

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
12/1/2014	12/1/2019	3/1/2011	DET	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.